

# .4 HP and 1/2 HP CAST IRON


## Submersible Sewage Pumps



WATER SYSTEMS



### MODELS 40EC, S1267



### FEATURES AND BENEFITS

- Rugged oil filled, 115V, 60Hz motor
- Thermal overload protects against overheating
- Epoxy coated, cast iron motor housing dissipates heat to ensure long life
- 2" discharge with 2" solids pumping capacity
- Bottom suction inlet with vortex impeller
- Waterproof power cord with grounded plug
- Ceramic and carbon seal for reliable service and extended life
- Temperature Rating: 130°F. (54°C.)

**.4 HP CAST IRON**  
**Submersible Sewage Pump**

STAR WATER SYSTEMS

- Premium vertical switch
- 2-in discharge passes 2-in solids

**103 GPM**

NON-CLOGGING VORTEX IMPELLER  
VERTICAL SWITCH

PUMPS 2-in. SOLIDS  
100% FACTORY TESTED

PERFORMANCE / RENDIMIENTO

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT) ALTURA DE DESCARGA POR ENCIMA DEL NIVEL DE BOMBEO (ELEVACION)	0 ft.	5 ft.	10 ft.	15 ft.
GALLONS PER MINUTE LITROS PER MINUTE	103 3883	90 3251	60 2161	23 832

2 YEAR LIMITED WARRANTY 115 V

starwatersystems.com

**1/2 HP CAST IRON**  
**Submersible Sewage Pump**

STAR WATER SYSTEMS

- Premium vertical switch
- 2-in discharge passes 2-in solids

**130 GPM**

NON-CLOGGING VORTEX IMPELLER  
VERTICAL SWITCH

PUMPS 2-in. SOLIDS  
100% FACTORY TESTED

PERFORMANCE / RENDIMIENTO

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT) ALTURA DE DESCARGA POR ENCIMA DEL NIVEL DE BOMBEO (ELEVACION)	0 ft.	5 ft.	10 ft.	15 ft.
GALLONS PER MINUTE LITROS PER MINUTE	130 4683	115 4129	85 3029	45 1588

2 YEAR LIMITED WARRANTY 115 V

starwatersystems.com

40EC  
S1267

UPC# 054757053352  
UPC# 054757054601



### PERFORMANCE

DISCHARGE HEIGHT ABOVE PUMPING LEVEL (LIFT)

	MODEL	HP	AMPS	0 ft.	5 ft.	10 ft.	15 ft.
GALLONS PER MINUTE	40EC	.4	9.4	103	90	60	23
	S1267	1/2	10.4	130	115	85	45

starwatersystems.com  
Toll Free Help Line  
1-800-742-5044

SW1631 A